

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1.-26. (Cancelled)

27. (Currently Amended) A lamination product comprising:

a substrate having pressure sensitive adhesive material coated on a first portion and a second portion of one side of the substrate;

release material covering ~~[[a]]~~ the first portion of the one side and exposing ~~[[a]]~~ the second portion of the one side, and

a transparent laminate secured to the substrate at the second portion of the one side with the pressure sensitive adhesive material, a portion of the laminate covering the first portion of the substrate and not being adhered to the substrate due to the release material,

wherein the release material is folded to expose the second portion, and

whereby a document can be secured in the lamination product by lifting the unadhered portion of the laminate, placing the document between the laminate and the substrate, removing the release material to expose the pressure sensitive adhesive material on the first portion of the substrate, and pressing the document and laminate against the exposed adhesive material of the first portion.

28. (Previously Presented) The product of claim 27, wherein the document is smaller than the first portion of the substrate, so that the laminate is secured to the substrate around all outer edges of the document.

~~28~~29. (Currently Amended) A method for laminating a document in a lamination product having

a substrate having pressure sensitive adhesive material coated on a first portion and a second portion of one side of the substrate,

release material covering ~~[[a]]~~ the first portion of the one side and exposing ~~[[a]]~~ the second portion of the one side, and

a transparent laminate secured to the substrate at the second portion of the one side

with the pressure sensitive adhesive material, a portion of the laminate covering the first portion of the substrate and not being adhered to the substrate due to the release material, wherein the release material is folded to expose the second portion, the method comprising:

- placing the document between the laminate and the substrate;
- removing the release material to expose the pressure sensitive adhesive material on the first portion of the substrate; and
- pressing the document and laminate against the exposed adhesive of the first portion.